

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Withdrawn) A multilayer capacitor comprising:
dielectric layers and
at least four types of, that is, first to fourth, internal conductor layers insulated from one another by said dielectric layer and arranged in an order from the first to fourth ones in a dielectric body;
wherein
each of said first to fourth internal conductor layers is formed with at least one cut part;
said internal conductor layers are formed with channel parts for current to flow in return by said respective cut parts; and
the channel parts in said internal conductor layers adjoining each other across said dielectric layer in the stacking direction carry current flowing in the reverse directions from each other.
2. (Withdrawn) The multilayer capacitor as set forth in claim 1, wherein plane shapes of said first internal conductor layer and said third internal conductor layer are symmetric each other with respect to the center of them.
3. (Withdrawn) The multilayer capacitor as set forth in claim 2, wherein plane shapes of said second internal conductor layer and said fourth internal conductor layer are symmetric each other with respect to the center of them.
4. (Withdrawn) The multilayer capacitor as set forth in claim 3, wherein
said first internal conductor layer has a first lead part led to a first side surface of said dielectric body; and

said third internal conductor layer has a third lead part led to a third side surface being opposite of said first side surface of said dielectric body.

5. (Withdrawn) The multilayer capacitor as set forth in claim 4, wherein said second internal conductor layer has a second lead part led to a second side surface being different from the first side surface and the third side surface of said dielectric body; and

said fourth internal conductor layer has a fourth lead part led to a fourth side surface on the opposite side of said second side surface of said dielectric body.

6. (Withdrawn) The multilayer capacitor as set forth in claim 5, wherein a width of said first lead part is substantially the same with the entire width of the first internal conductor layer formed with said cut part; and

a width of said third lead part is substantially the same with the entire width of the third internal conductor layer formed with said cut part.

7. (Withdrawn) The multilayer capacitor as set forth in claim 6, wherein the first side surface of said dielectric body is attached with a first terminal electrode connected to said first lead part; and

the third side surface of said dielectric body is attached with a third terminal electrode connected to said third lead part.

8. (Withdrawn) The multilayer capacitor as set forth in claim 7, wherein said first terminal electrode and said third terminal electrode have the same or wider width compared with those of said first lead part and third lead part.

9. (Withdrawn) The multilayer capacitor as set forth in claim 8, wherein the second side surface of said dielectric body is attached with a second terminal electrode connected to said second lead part; and

the fourth side surface of said dielectric body is attached with a fourth terminal electrode connected to said fourth lead part.

10. (Withdrawn) The multilayer capacitor as set forth in claim 9, wherein
a width of said second lead part is substantially the same as that of said channel part separated by the cut part of said second internal conductor layer; and
a width of said fourth lead part is substantially the same as that of said channel part separated by the cut part of said fourth internal conductor layer.

11. (Withdrawn) The multilayer capacitor as set forth in claim 10, wherein
said second lead part is led to the substantial center portion of said second side surface; and

said fourth lead part is led to the substantial center of said fourth side surface.

12. (Withdrawn) The multilayer capacitor as set forth in claim 11, wherein
a width of said second terminal electrode is substantially the same as or wider than that of said second lead part but narrower than that of said second side surface; and

a width of said fourth terminal electrode is substantially the same as that of said second terminal electrode.

13. (Withdrawn) The multilayer capacitor as set forth in any one of claims 1 to 12, wherein said first to fourth internal conductor layers are stacked in this order repeatedly for a plurality of times in the stacking direction respectively across said dielectric layers.

14. (Withdrawn) The multilayer capacitor as set forth in any one of claims 1 to 12, wherein a plane shape of said cut part has a substantial L-shape.

15. (Withdrawn) The multilayer capacitor as set forth in claim 14, wherein a width of said cut part is 1/10 to 1/3 of a width of said internal conductor layer.

16. (Currently Amended) A multilayer capacitor comprising:
dielectric layers and

at least eight types of, that is, first to eighth, internal conductor layers insulated from one another by said dielectric layer and arranged in an order from the first to eighth ones in a dielectric body;

wherein

each of said first to eighth internal conductor layers is formed with ~~at least one cut part;~~only one straight line shaped cut part;

each of said internal conductor layers is formed with a channel part for a current to flow in return by said cut part; and

the channel parts in said internal conductor layers adjoining each other across said dielectric layer in the stacking direction carry current flowing in the reverse directions from each ~~other.~~ other.

plane shapes of the first internal conductor layer and the fifth internal conductor layer being symmetric to each other with respect to a center of each other;

plane shapes of the second internal conductor layer and the sixth internal conductor layer being symmetric to each other with respect to a center of each other;

plane shapes of the third internal conductor layer and the seventh internal conductor layer being symmetric to each other with respect to a center of each other;

plane shapes of the fourth internal conductor layer and the eighth internal conductor layer being symmetric to each other with respect to a center of each other.

the first internal conductor layer has a first lead part led to the first side surface of the dielectric body;

the second internal conductor layer has a second lead part led to a different position from the first lead part on the first side surface of the dielectric body;

the third internal conductor layer has a third lead part led to the second side surface being different from the first side surface and the third side surface of the dielectric body;

the fourth internal conductor layer has a fourth lead part led to a different position from the third lead part on the second side surface of the dielectric body;

the fifth internal conductor layer has a fifth lead part led to the third side surface on the opposite side of the first side surface of the dielectric body;

the sixth internal conductor layer has a sixth lead part led to a different position from the fifth lead part on the third side surface of the dielectric body;

the seventh internal conductor layer has a seventh lead part led to the fourth side surface on the opposite side of the second side surface of the dielectric body; and

the eighth internal conductor layer has an eighth lead part led to a different position from the seventh lead part on the fourth side surface of the dielectric body.

17-18. (Canceled).

19. (Currently Amended) The multilayer capacitor as set forth in ~~claim 18~~, claim 16, wherein a width of each of said lead parts is $1/3$ to $1/4$ of a width of said channel part in each of said internal conductor layers.

20. (Currently Amended) The multilayer capacitor as set forth in ~~claim 18~~, claim 16, wherein

a first terminal electrode and a second terminal electrode respectively connected to said first lead part and second lead part are attached to the first side surface of said dielectric body;

a third terminal electrode and a fourth terminal electrode respectively connected to said third lead part and fourth lead part are attached to the second side surface of said dielectric body;

a fifth terminal electrode and a sixth terminal electrode respectively connected to said fifth lead part and sixth lead part are attached to the third side surface of said dielectric body; and

a seventh terminal electrode and an eighth terminal electrode respectively connected to said seventh lead part and eighth lead part are attached to the fourth side surface of said dielectric body.

21. (Currently Amended) The multilayer capacitor as set forth in ~~any one of claims 16 to 20,~~ claim 16, wherein said first to eighth internal conductor layers are stacked in this order repeatedly for a plurality of times in the stacking direction respectively across said dielectric layers.

22. (Canceled).

23. (Currently Amended) The multilayer capacitor as set forth in ~~claim 22,~~ claim 16, wherein a width of said cut part is 1/10 to 1/3 of a width of said internal conductor layer.

24. (Withdrawn) A multilayer capacitor comprising:
dielectric layers, and
at least four types of, that is, first to fourth, internal conductor layers insulated from one another by said dielectric layer and arranged in an order from the first to eighth ones in a dielectric body,

a fifth internal conductor layer formed on the dielectric layer formed with said first internal conductor layer, adjacent to said first internal conductor layer on the same plane to be a pattern isolated from said first internal layer;

a sixth internal conductor layer formed on the dielectric layer formed with said second internal conductor layer, adjacent to said second internal conductor layer on the same plane to be a pattern isolated from said second internal layer;

a seventh internal conductor layer formed on the dielectric layer formed with said third internal conductor layer, adjacent to said third internal conductor layer on the same plane to be a pattern isolated from said third internal layer; and

an eighth internal conductor layer formed on the dielectric layer formed with said fourth internal conductor layer, adjacent to said fourth internal conductor layer on the same plane to be a pattern isolated from said fourth internal layer;

wherein

each of said first to eighth internal conductor layers is formed with at least one cut part;

each of said internal conductor layers is formed with a channel part for a current to flow in return by said cut part; and

the channel parts in said internal conductor layers adjoining each other across said dielectric layer in the stacking direction carry current flowing in the reverse directions from each other.

25. (Withdrawn) The multilayer capacitor as set forth in claim 24, wherein plane shapes of said first internal conductor layer and said third internal conductor layer are symmetric each other with respect to the center of them;

plane shapes of said second internal conductor layer and said fourth internal conductor layer are symmetric each other with respect to the center of them;

plane shapes of said fifth internal conductor layer and said seventh internal conductor layer are symmetric each other with respect to the center of them; and

plane shapes of said sixth internal conductor layer and said eighth internal conductor layer are symmetric each other with respect to the center of them.

26. (Withdrawn) The multilayer capacitor as set forth in claim 24, wherein

plane shapes of said first internal conductor layer and said fifth internal conductor layer are symmetric each other with respect to the center of a space between them;

plane shapes of said second internal conductor layer and said sixth internal conductor layer are symmetric each other with respect to the center of a space between them;

plane shapes of said third internal conductor layer and said seventh internal conductor layer are symmetric each other with respect to the center of a space between them;

and

said fourth internal conductor layer and said eighth internal conductor layer are symmetric each other with respect to the center of a space between them.

27. (Withdrawn) The multilayer capacitor as set forth in claim 24, wherein

said first internal conductor layer has a first lead part led to the first side surface of said dielectric body;

said fifth internal conductor layer has a fifth lead part led to the third side surface on the opposite side of the first side surface of said dielectric body;

said second internal conductor layer has a second lead part led to a different position from said first lead part on the first side surface of said dielectric body;

said sixth internal conductor layer has a sixth lead part led to a different position from said fifth lead part on the third side surface of said dielectric body;

said third internal conductor layer has a third lead part led to a different position from said fifth lead part and sixth lead part on the third side surface of said dielectric body;

said seventh internal conductor layer has a seventh lead part led to a different position from said first lead part and second lead part on the first side surface of said dielectric body;

said fourth internal conductor layer has a fourth lead part led to a different position from said third lead part, fifth lead part and sixth lead part on the third side surface of said dielectric body; and

said eighth internal conductor layer has a eighth lead part led to a different position from said first lead part, second lead part and seventh lead part on the first side surface of said dielectric body.

28. (Withdrawn) The multilayer capacitor as set forth in claim 27, wherein a width of each of said first to eighth lead parts is the same as or narrower than that of the channel part in each of said internal conductor layers.

29. (Withdrawn) The multilayer capacitor as set forth in claim 27, wherein said dielectric body has a parallelepiped shape having said second side surface and fourth side surface being different from said first side surface and third side surface; and widths of the first side surface and third side surface are wider than those of said second side surface and fourth side surface.

30. (Withdrawn) The multilayer capacitor as set forth in claim 29, wherein the first side surface of said dielectric body is attached with a first terminal electrode connected to said first lead part, a second terminal electrode connected to said second lead part, a seventh terminal electrode connected to said seventh lead part and an eighth terminal electrode connected to said eighth lead part; and

the third side surface of said dielectric body is attached with a third terminal electrode connected to said third lead part, a fourth terminal electrode connected to said fourth lead part, a fifth terminal electrode connected to said fifth lead part and an sixth terminal electrode connected to said sixth lead part.

31. (Withdrawn) The multilayer capacitor as set forth in any one of claims 24 to 30, wherein said first to fourth internal conductor layers are stacked in this order repeatedly for a plurality of times in the stacking direction respectively across said dielectric layers; and said fifth to seventh internal conductor layers are stacked in this order repeatedly for a plurality of times in the stacking direction respectively across said dielectric layers.

32. (Withdrawn) The multilayer capacitor as set forth in any one of claims 24 to 30, wherein

said cut parts formed on said first, fifth, third and seventh internal conductor layers have a substantial L-shape; and

said cut parts formed on said second, sixth, fourth and eighth internal conductor layers have a substantial linear shape.

33. (Withdrawn) The multilayer capacitor as set forth in claim 32, wherein a width of said cut part is $1/10$ to $1/3$ of a width of said internal conductor layer.